

MIXER 80



Concrete mixer is a new idea for an item that can be used for various employments: concrete preparation, fodder mixing, vegetables and dried fruits washing.

The main characteristics are the following:

- The mixer cone is made of 3 mm steel sheet without any welded joints, bolted together, allowing spaces reduction and the possibility of substituting the most exposed parts to wear
- Frame designed to be attached to all types of tractor
- Chain transmission drive system, with a 10:1 reduction ratio, is protected by a steel housing with an easy access for the maintenance
- Loading and unloading operations are facilitated by the large mouth of the front hopper and also by the simplicity of the hydraulic cylinder
- The machine is painted with a high quality epoxy varnish with successive backing at 150° C ensuring maximum protective life and less wear problems.

Mixer 80 è la nuova idea per un attrezzo che può essere utilizzato per diversi impieghi: preparazione calcestruzzo, miscelazione dei mangimi, lavaggio di ortaggi e frutta secche.

Le caratteristiche principali sono le seguenti:

- Cono della betoniera formato da acciaio di 3 mm senza saldature, ma con parti imbullonate che permette riduzione di spazi e intercambiabilità delle parti
- Telaio studiato e realizzato in modo da consentire il montaggio su trattori di qualunque modello
- Trasmissione a catena con rapporto 10-1 protetta da un carter in acciaio con facile accesso per manutenzione
- La grande apertura della tramoggia anteriore facilita le operazione di carico e semplifica la corsa durante l'operazione di scarico
- La verniciatura come per tutti i prodotti Cosmo viene effettuata con vernice epossidica a forno a 150° C con l'applicazione della mano di fondo a bagno, garantendo una grande protezione e una lunga durata della macchina.



TECNICAL DATA / DATI TECNICI

CAPACITY gallon / CAPACITÀ lt	71 1/2 cement sack - 320 1/2 sacco di cemento		
DIMENSIONS (ft) / DIMENSIONI (mm)	2,82 width/860 larg	3,05 length/930 lung	3,12h/950h
WEIGHT lbs / PESO (kg)	220/100		
DIAMETER / DIAMETRO	1,45/440		
PTO / CARDANO	1,18 inch w/splint pin - 30 mm con spina elastica		
HYDRAULIC HITCH / ATTACCO IDRAULICO	18x1,5		
HYDRAULIC PRESSURE Bars(atm)/PRESSIONE IDRAULICA Bars(atm)	MIN 50	MAX 140	
ROTATION VELOCITY / VELOCITÀ DI ROTAZIONE	MIN 250	MAX 300 r.p.m. / giri/min	
TRANSMISSION / TRASMISSIONE	10/1		

COSMO s.r.l.

Loc. Roata Raffa, 64 - Z.I. - 12022 Busca (CN) - Italy - Phone +39.0171.946654 / 55 - Fax +39.0171.946723

Web site: www.cosmosrl.com - E-mail: imcosmo@cosmosrl.com

